

# Barbarian...durable cubicles for high traffic areas

Decra Barbarian, as the name implies, is an extremely tough cubicle system combining discreet aluminium pilasters with solid grade (compact) laminate panels to provide the ultimate solution for high-traffic environments like shopping malls, stadia, schools and colleges.

Flat fronted aluminium pilasters are anchored at the floor, providing superb rigidity and removing the need for a pedestal support.

DDA compliant locks in either SAA or S/Steel with matching accessories are the hardware options.

S/Steel anti penetration panels can be provided wherever conditions demand them.

Some sample finishes are shown on this data sheet. Many more are available.

**Decra Ltd**  
**34 Forest Business Park**  
**Argall Avenue**  
**London. E10 7FB**  
**Tele: 020 8520 4371**  
**Fax: 020 8521 0605**  
**Email: sales@decraltd.co.uk**  
**www.toiletcubicles.org**



# Colours...



# NBS spec...

K32 Panel Cubicles

## 120A PANEL CUBICLES

- **Type:** standard height to contractor design and CA approval of appearance. Preferred Suppliers and Products.
- **Manufacturer:** Decra Ltd - 020 8520 4371. - Product reference: Barbarian toilet cubicles.
- **Panels: Dividing and Rear Ducts**
  - Height (overall): 1960mm above f.f.l. 2400mm for full height duct panels.
  - Floor clearance: 150mm.
  - Core material: solid resin (compact) grade laminate.
  - Thickness: 13mm.
  - Facings: melamine protected colour.
  - Colour: to be selected from manufacturer's standard colour ranges.
  - Edge treatment: black self edged - machined to a crescent with all exposed corners radiused for safety.
- **Panels Pilasters**
  - Height (overall): 1960mm above f.f.l.
  - Floor clearance: none.
  - Core material: anodised aluminium.
  - Thickness: 2.5mm (approx) extruded sections.
  - Facings: satin finish.
  - Colour: SA aluminium.
  - Edge treatment: radiused aluminium.
- **Panels: Doors**
  - Height: 1772mm (1922mm above f.f.l.).
  - Floor clearance: 150mm.
  - Core material: solid resin (compact) grade laminate.
  - Thickness: 13mm.
  - Facings: melamine protected colour.
  - Colour: to be selected from manufacturer's standard colour ranges.
  - Edge treatment: as dividing panels.
- **Fittings Generally**
  - Headrail: satin anodised aluminium.
  - Pedestals: none.
- **Accessories**
  - DDA compliant anodised aluminium lock and indicator.
  - Buffered coat hook.
  - Pull handles (for ambulant disabled cubicles).
- **Other requirements:** none.